

## Declaration of Performance Timba 14mm T&G Chevron Oak

No. BUA 3W 01/08/2019

Unique product identification code:	BVU
2. Intended use or uses:	The three-layer floorboards are designed for installation in inside rooms . Suitable for installation on top of a hydronic or electric underfloor heating system. Installation by gluing to the subfloor. Pre-coated with varnish or oil and ready for use immediately after installation.
3. Manufacturer:	B2B Wood Products Ltd / Timba Floors & Boards Unit 3A Linden Park Industrial Estate Wherdohl Way Consett County Durham DH8 6SZ
4. Authorised representative:	Not Applicable
System(s) for assessment and verification of constancy of performance:	3
6. Harmonised standard:	EN 14342:2013  The following notified bodies:  1. SATRA Technology Centre Limited, Wyndham Way, Telford Way, Kettering, Northamptonshire NN16 8SD, United Kingdom, Notification body: 0321  performed type examination according to system 3 and issued type examination reports.

7. Declared Performance:	Essential Features:	Performance	Harmonised Technical Specifications
	Reaction to fire:	Dfl-s1	
	Minimum density:	500kg/m³	
	Minimum thickness:	14mm	
	Formaldehyde emissions:	E-1	
	Pentachlorophenol emissions:	NPD	EN 14342:2013
	Thermal conductivity:	0.14 W/mK	
	Slip:	NPD	
	Biological stability:	NPD	

Relevant or special technical documentation:	Product technical specifications

The performance of the above-described product corresponds to the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the said manufacturer.

Benjamin Muxworthy Supply Chain Manager

Name & Title

Durham,, UK 24th June 2020

Place & Date of Issue

Address:

Unit 1, Priority Freight Logistics Seven Stars Industrial Estate Coventry, CV3 4LB

Contact Us:

(0333) 360 3600 sales@timbafloor.com www.timbafloor.com

Signature

@timbafloor







A B2B Wood **Products Company**